

TB1S~TB10S

Surface Mount Flat Bridge Rectifier

Reverse Voltage - 100 to 1000 V


Forward Current - 0.8 A

Features

- Ideal for printed circuit board
- Glass passivated chip
- Reliable low cost construction utilizing molded plastic technique
- Small size, simple installation

Mechanical Data

- **Terminal:** Plated leads solderable per MIL-STD 202E, method 208C
- **Case:** UL-94 Class V-0 recognized flame retardant epoxy
- **Polarity:** Polarity symbol marked on body
- **Marking Code:** TB10S



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical characteristics

Single-phase, half-wave, 60 Hz, resistive or inductive load rating at 25°C, unless otherwise stated, for capacitive load, derate current by 20 %.

Parameter	Symbols	TB1S	TB2S	TB4S	TB6S	TB8S	TB10S	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current on Glass-epoxy P.C.B.	$I_{F(AV)}$	0.8						A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	25						A
Maximum Instantaneous Forward Voltage at Forward Current 0.4 A	V_F	0.95						V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	5 100						μA
Typical Thermal Resistance Junction to Lead On Glass-epoxy P.C.B.	$R_{\theta JL}$ $R_{\theta JA}$	42 88						$^{\circ}C/W$
Operating and Storage Temperature Range	T_j, T_{stg}	- 55 to + 150						$^{\circ}C$

TOP DYNAMIC



ISO14001 : 2004 Certificate No. 121505007
 ISO 9001 : 2008 Certificate No. 5014012
 OHSAS 18001 : 2007 Certificate No. 05131508006
 IECQ QC 080000 Certificate No. EC31W0274482

Dated: 28/09/2016 Rev: 07

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- TYPICAL FORWARD CHARACTERISTICS




FIG.3- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.4- FORWARD POWER DISSIPATION




FIG.5- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

